



# Florian Schulz

## One 80


### Version

- brass burnished lacquered
- brass dark burnished lacquered
- brass matt brushed lacquered
- brass polished lacquered
- brass polished unlacquered
- chrome-plated brass
- copper-plated brass lacquered
- copper-plated brass matt brushed lacquered
- nickel-plated brass
- brass nickel-plated lacquered
- brass nickel-plated matt brushed

### Voltage

- 230 - 240
- 125 (special US version)

## Technical details

<b>Country of Manufacture</b>	 Germany
<b>Manufacturer</b>	Florian Schulz
<b>Designer</b>	Jens Schump
<b>Year of design</b>	2017
<b>Protection class / IP rating</b>	IP20
<b>Contents of the package</b>	LED
<b>voltage suitability</b>	110 - 240 Volt
<b>Diameter in cm</b>	80
<b>material</b>	brass
<b>Height adjustment</b>	height determinable
<b>dimming</b>	on site dimmable with a trailing edge dimmer
<b>Wattage</b>	108 W
<b>LED</b>	inclusive
<b>Colour Rendering Index</b>	>95
<b>Luminous flux in lm</b>	4,200
<b>Color temperature in Kelvin</b>	2,700 extra warm white
<b>canopy dimensions</b>	25 cm
<b>light distribution</b>	directly and indirectly
<b>total height</b>	100 - 200 cm
<b>Dimensions</b>	H 2 cm   Ø 80 cm

## Description

The VS Manufaktur One 80 pendant lamp has an annular lamp shape with a diameter of 80 cm. The height of the lamp is 2 cm. The light of the lamp is emitted both downwards as well as upwards. The maximum height of the lamp is 200 cm and can be adjusted up to a height of at least 100 cm. On request, versions with a different suspension height are also available. The following surfaces are offered: brass nickel-plated, polished lacquered, chrome-plated, nickel-plated matt brushed, burnished lacquered, dark burnished lacquered, copper-plated, nickel-plated lacquered, polished unlacquered, copper-plated matt brushed lacquered and matt brushed lacquered. An LED with diffuser is integrated. This LED has a power of 43 watts at a colour temperature of 2,700 Kelvin extra warm white. Only the 230-240 volt pendant lamp can be dimmed on site. The 110 - 125 volt version is supplied here as a non-dimmable version.