



# Mawa

## Bullauge 6 pendant mounting with uplight

### Durchmesser in cm

- 45
- 60
- 80
- 120

### Technical details

<b>Country of Manufacture</b>	 Germany
<b>Manufacturer</b>	Mawa
<b>Designer</b>	Martin Wallroth
<b>surface</b>	weiß matt / white matt
<b>protection</b>	IP20
<b>Scope of delivery</b>	LED
<b>voltage suitability</b>	230 - 240 Volt
<b>material</b>	acrylic glass, aluminum
<b>cable length</b>	250 cm
<b>height adjustment</b>	height determinable
<b>dimming</b>	dimnable with a trailing edge dimmer and with a leading edge dimmer
<b>LED</b>	inclusive
<b>light distribution</b>	directly and indirectly
<b>Dimensions</b>	H 10 cm

### Description

The Mawa Bullauge 6 pendant mounting with uplight emits light both upwards and downwards. The pendant light is available with a diameter of 45 cm, 60 cm, 80 cm or 120 cm. As standard, the lamp is made of aluminum in powder-coated white matt. On request it can also be supplied in other RAL colours. The even distribution of the LEDs and the opaque, satinised plexiglass diffuser ensure a very homogeneous, luminous surface at the bottom of the lamp. The three smaller versions of Bullauge 6 pendant mounting with uplight are suspended on three parallel cables, the largest lamp on four parallel cables. The cables have a maximum length of 250 cm and can be shortened if necessary. On request, the lamp is also available with other cable lengths or without uplight.

The Bullauge 6 can be dimmed with a leading edge or trailing edge phase dimmer. On request, it is also available DALI dimmable. It is also offered with a different diameter up to 120 cm on request. As standard, the three smaller lamps are supplied with a colour temperature of 2,700 Kelvin extra warm white, on request they are also available with 3,000 Kelvin warm white. The pendant lamp with a diameter of 120 cm has a colour temperature of 3,000 Kelvin warm white.