



# Bover

## Drop Linear PF/09L

#### Farbe

- green
- blue
- matt white
- transparent

### **Technical details**

ManufacturerBoverDesignerChristophe MathieuYear of design2017protectionIP20Scope of deliveryLEDvoltage suitability110 - 240 Voltmaterialaluminum, Iron, polycarbonatedimmingDALI dimmableWattage28.8 WLEDinclusiveColour Rendering Index90Color temperature in Kelvin12 cmShade diameter11 cmShade height11 cmBulb exchangeat the manufacturer / at the factoryTotal luminous flux in Im3,348Ight distributionroom lightCeiling rail length54 cm	Country of Manufacture	Spain
Year of design2017protectionIP20Scope of deliveryLEDvoltage suitability110 - 240 Voltmaterialaluminum, Iron, polycarbonatedimmingDALI dimmableWattage28.8 WLEDinclusiveColour Rendering Index90Color temperature in Kelvin2,700 extra warm whiteShade diameter11 cmShade height11 cmShade height3,348light distributionroom lightKeiling rail length180 cm	Manufacturer	Bover
ProtectionIP20Scope of deliveryLEDvoltage suitability110 - 240 Voltmaterialaluminum, Iron, polycarbonatedimmingDALI dimmableWattage28.8 WLEDinclusiveColour Rendering Index90Color temperature in Kelvin2,700 extra warm whitecanopy dimensions12 cmShade diameter11 cmShade height3,348light distributionroom lightCeiling rail length180 cm	Designer	Christophe Mathieu
Scope of deliveryLEDvoltage suitability110 - 240 Voltmaterialaluminum, Iron, polycarbonatedimmingDALI dimmableWattage28.8 WLEDinclusiveColour Rendering Index90Color temperature in Kelvin2,700 extra warm whitecanopy dimensions12 cmShade diameter11 cmShade height11 cmbulb exchange3,348light distributionroom lightCeiling rail length180 cm	Year of design	2017
voltage suitability110 - 240 Voltmaterialaluminum, Iron, polycarbonatedimmingDALI dimmableWattage28.8 WLEDinclusiveColour Rendering Index90Color temperature in Kelvin2,700 extra warm whitecanopy dimensions12 cmShade diameter11 cmShade height3,348light distributionxoom lightColour function3,348	protection	IP20
materialaluminum, Iron, polycarbonatematerialaluminum, Iron, polycarbonatedimmingDALI dimmableWattage28.8 WLEDinclusiveColour Rendering Index90Color temperature in Kelvin2,700 extra warm whitecanopy dimensions12 cmShade diameter11 cmShade height11 cmbulb exchangeat the manufacturer / at the factoryTotal luminous flux in Im3,348light distributionroom lightCeiling rail length180 cm	Scope of delivery	LED
dimmingDALI dimmableWattage28.8 WLEDinclusiveColour Rendering Index90Color temperature in Kelvin2,700 extra warm whitecanopy dimensions12 cmShade diameter11 cmShade height11 cmbulb exchangeat the manufacturer / at the factoryTotal luminous flux in Im3,348light distributionroom lightCeiling rail length180 cm	voltage suitability	110 - 240 Volt
Wattage28.8 WLEDinclusiveColour Rendering Index90Color temperature in Kelvin2,700 extra warm whitecanopy dimensions12 cmShade diameter11 cmShade height11 cmbulb exchangeat the manufacturer / at the factoryTotal luminous flux in Im3,348light distributionroom lightCeiling rail length180 cm	material	aluminum, Iron, polycarbonate
LEDinclusiveColour Rendering Index90Color temperature in Kelvin2,700 extra warm whitecanopy dimensions12 cmShade diameter11 cmShade height11 cmbulb exchangeat the manufacturer / at the factoryTotal luminous flux in Im3,348light distributionroom lightCeiling rail length180 cm	dimming	DALI dimmable
Colour Rendering Index90Color temperature in Kelvin2,700 extra warm whitecanopy dimensions12 cmShade diameter11 cmShade height11 cmbulb exchangeat the manufacturer / at the factoryTotal luminous flux in Im3,348light distributionroom lightCeiling rail length180 cm	Wattage	28.8 W
Color temperature in Kelvin2,700 extra warm whitecanopy dimensions12 cmShade diameter11 cmShade height11 cmbulb exchangeat the manufacturer / at the factoryTotal luminous flux in Im3,348light distributionroom lightCeiling rail length180 cm	LED	inclusive
canopy dimensions12 cmShade diameter11 cmShade height11 cmbulb exchangeat the manufacturer / at the factoryTotal luminous flux in lm3,348light distributionroom lightCeiling rail length180 cm	Colour Rendering Index	90
Shade diameter11 cmShade height11 cmbulb exchangeat the manufacturer / at the factoryTotal luminous flux in lm3,348light distributionroom lightCeiling rail length180 cm	Color temperature in Kelvin	2,700 extra warm white
Shade height11 cmbulb exchangeat the manufacturer / at the factoryTotal luminous flux in Im3,348light distributionroom lightCeiling rail length180 cm	canopy dimensions	12 cm
bulb exchangeat the manufacturer / at the factoryTotal luminous flux in Im3,348light distributionroom lightCeiling rail length180 cm	Shade diameter	11 cm
Total luminous flux in Im3,348light distributionroom lightCeiling rail length180 cm	Shade height	11 cm
light distributionroom lightCeiling rail length180 cm	bulb exchange	at the manufacturer / at the factory
Ceiling rail length 180 cm	Total luminous flux in lm	3,348
0 0	light distribution	room light
total height 54 cm	Ceiling rail length	180 cm
total height	total height	54 cm

#### Description

The Drop Linear PF/09L from the Spanish lighting manufacturer Bover is an LED pendant lamp with nine individual pendants mounted on a black 180 cm long aluminium ceiling rail. The distance between the individual pendants is 20 cm. The power connection is located on a decentralised canopy with a diameter of 12 cm. The glass of the Bover Drop Linear PF/09L can be removed for replacement or cleaning. The nine lamp shades each have a diameter of 10.7 cm and are 11.2 cm high. This LED pendant lamp is available in the shade colours transparent, matt white, green and blue. The distance between the ceiling and the lower edge of the individual pendant lamps is 54 cm. 13 different cable lengths are available on request. You can therefore choose the length of your lamp to suit your individual requirements. When ordering, please specify the required length/distance between the ceiling and the lower edge of the lamp under the item Order overview in the Order comments field.

K-Meral GmbH & Co. KG | Sachsenweg 9 | Hambau / Öko-Zentrum NRW / Halle 4 | 59073 Hamm Tel.: +49 (0) 2381 - 905 9350 | Fax: +49 (0) 2381 - 905 9310 | info@1001lights.com