



Technical details

Country of Manufacture	Italy
Manufacturer	Catellani & Smith
Designer	Enzo Catellani
Year of design	2018
protection	IP44
Scope of delivery	LED
voltage suitability	230 - 240 Volt
material	brass, glass
socket/light fixture	G4
LED	inclusive
Colour Rendering Index	80
Color temperature in Kelvin	2,700 extra warm white
bulb exchange	on site itself
system performance	3 x 1 Watt
Total luminous flux in lm	225
Dimensions	H 45 + 2 x 75 cm

Catellani & Smith Syphaduepassi Set 3

Description

The Catellani & Smith Syphaduepassi Set 3 consists of three complete outdoor floor lamps, ready for connection, with all necessary accessories. With the Quick Connectors System by Catellani & Smith, the three lamps can be easily connected together. Only a single power connection is required for installation. All necessary connectors are included. The set contains:

- One lamp with a height of 45 cm
- two lamps with a height of 75 cm
- an extension cable with a length of 500 cm
- a driver necessary for lamp operation
- a connection cable for the power supply.

The Syphaduepassi outdoor floor lamps can be fixed with their ground spike up to 25 cm into the ground. The heights of the lamps (45 cm and 75 cm) are without ground spike. The glass lens of the lamps focuses the light and ensures glare-free lighting. Each lamp has a bendable brass lamp rod which can be realigned if necessary. The Syphaduepassi lamps are protected to IP44 against splashing water from all sides and solid foreign bodies with a diameter of 1 mm or more. Their lamp rods are dust-tight with IP65 protection and protected against strong jets of water from any angle. Drivers and extension cables are protected to IP67 against temporary immersion. The Syphaduepassi is also available in sets of one complete lamp and sets of two, four, five or nine complete lamps.

K-Meral GmbH & Co. KG | Sachsenweg 9 | Hambau / Öko-Zentrum NRW / Halle 4 | 59073 Hamm Tel.: +49 (0) 2381 - 905 9350 | Fax: +49 (0) 2381 - 905 9310 | info@1001lights.com

www.1001lights.com