

# Lichtlauf

## UpLight Down




### Durchmesser in cm

- 50
- 40
- 30

### Kabelfarbe

- red
- white
- grey

## Technical details

<b>Country of Manufacture</b>	 Germany
<b>Manufacturer</b>	Lichtlauf
<b>Designer</b>	Christoph Matthias
<b>Year of design</b>	2012
<b>Protection class / IP rating</b>	IP20
<b>Contents of the package</b>	Leuchtmittel/ Bulb
<b>voltage suitability</b>	110 - 240 Volt
<b>material</b>	polyethylene, Textile
<b>surface</b>	white
<b>cable length</b>	250 cm
<b>dimming</b>	dimmable on site
<b>Base / Socket</b>	E27
<b>Switchability</b>	on the lead
<b>Power (max. Watt)</b>	70 Watt
<b>bulb exchange</b>	on site itself

## Description

The UpLight Down light run is the floor version of the UpLight lamp. Supplemented with a stand ring and foot switch, this lamp illuminates low room zones with its mild light, creating a special and variable lighting mood. The white hollow sphere made of resistant and high-quality polyethylene is available in three different diameters, the textile cable in three different colours. The UpLight Down by Lichtlauf has an E27 ceramic socket and can be operated with conventional halogen bulbs as well as with LED retrofit bulbs. This portable lamp is available with a diameter of 30 cm, 40 cm or 50 cm. The textile 2.5 m cable is optionally available in white, red or grey. On request, the textile cable is also available in other colours and lengths.