




# Byok

## Squadra Mono 200

### Oberfläche

- Aluminio pulido
- aluminio mate
- Aluminio negro
- satén polvo blanco recubierto

### Technical details

<b>País de origen</b>	
<b>Fabricante</b>	Byok
<b>Diseñador</b>	Kai Byok
<b>Índice de protección / Protección IP</b>	IP20
<b>Contenido del paquete</b>	LED
<b>entrada de tensión</b>	230 - 240 Volt
<b>material</b>	aluminio
<b>longitud del cable</b>	250 cm
<b>Ajuste de altura</b>	altura determinada
<b>Atenuación</b>	Regulable en el sitio con control de fase inversa
<b>LED</b>	incluyendo
<b>Indice de reproduccion cromatica</b>	90
<b>Temperatura de color en grados Kelvin</b>	2.700 extra blanco cálido
<b>El rendimiento del sistema</b>	12 x 3,6 Watt
<b>Flujo total luminoso en lm</b>	3.670
<b>distribución de la luz</b>	directamente
<b>Dimensions</b>	H 4 cm   B 9 cm   L 200 cm

### Descripción

The Byok Squadra Mono 200 is a pendant lamp with a clear and timeless design. The Squadra Mono consists of one element. Through this, the characteristic alignment is created. The hollow profile used, gets its effect through the mounting hooks installed to one side. The filigree steel ropes underline the purist optics.

The profile endings come with matt transparent and translucent end caps. That's why the Byok Squadra Mono 200 sets additional highlights when switched on. The integrated LEDs can be **dimmed on site with a trailing edge phase dimmer**. On request, they are also available with gesture control and Dim2Warm technology. With gesture control, the light is dimmed by holding the hand flat under the lamp. With Dim2Warm technology, the light takes on a warmer colour when dimmed. When dimmed, the light colour of the LEDs changes from 2,700 Kelvin extra warm white to 2,100 Kelvin extra warm white. The LEDs are placed in sockets enabling to singly exchange the bulbs.