

Catellani & Smith

Fil de Fer Pendant LED 100


Oberfläche

- aluminio natural
- oro

Voltage

- 230 - 240
- 125 (versión especial de Estados Unidos)

Technical details

| | |
|--|--|
| País de la Fabricación |  Italia |
| fabricante | Catellani & Smith |
| diseñador | Enzo Catellani |
| año | 2002 |
| protección | IP20 |
| Volumen de suministro | LED |
| entrada de tensión | 110 - 240 Volt |
| Diámetro en cm | 100 |
| material | aluminio |
| longitud del cable | 170 cm |
| ajuste de altura | altura determinada |
| Atenuación | Regulable en el sitio con control de fase inversa |
| base/portalámparas | G4 |
| LED | incluyendo |
| Indice de reproducción cromática | 80 |
| Temperatura de color en grados Kelvin | 2.700 extra blanco cálido |
| Dimensiones del dosel | 21 cm |
| reemplazo de la bombilla: | en el sitio mismo |
| El rendimiento del sistema | 24 x 1 Watt |
| Flujo total luminoso en lm | 1.800 |
| Dimensions | Ø 100 cm |

Descripción

This Catellani & Smith Fil de Fer 100 is an LED pendant light, which is shaped like a sphere. It is available in two surfaces: natural aluminum or gold. The lamp with the surface natural aluminum is made of untreated aluminum wire and therefore acts silver. For the golden version, the aluminum wire is anodized in gold. The diameter is for this lamp 100 cm.

As lamps, 24 LED lamps are used with a power of 1 watts. The Fil de Fer 100 Pendant LED 100 is on site dimmable. The dome-shaped canopy has dimensions of 21 x 10.5 cm. The cable of this light is available in a length of 170 cm, but can be shortened if necessary.