



LDM

Drop Move Duo Surface-mounted

Oberfläche

- aluminio mate
- aluminio pulido
- negro
- bronce
- blanco

Dimmbarkeit

- DALI regulable
- Regulable en el sitio con control de fase inversa
- con módulo Casambi

Technical details

| | |
|--|--|
| País de la Fabricación |  Alemania |
| fabricante | LDM |
| diseñador | Jürgen Glauner |
| protección | IP20 |
| Volumen de suministro | LED |
| entrada de tensión | 230 - 240 Volt |
| materi al | aluminio |
| Color del cable | transparente |
| longitud del cable | 50 - 200 cm |
| ajuste de altura | altura ajustable |
| LED | incluyendo |
| Indice de reproduccion cromatica | >95 |
| Temperatura de color en grados Kelvin | Dim to warm |
| Dimensiones del dosel | Longitud 80 cm, anchura 6,5 cm, altura 2,7 cm |
| Diamètre de l'ombre | 7 cm |
| Altura de pantalla | 19 cm |
| reemplazo de la bombilla: | en el fabricante / en la fabrica |
| El rendimiento del sistema | 2 x 8,75 Watt |
| Flujo total luminoso en lm | 1.562 |

Descripción

The LDM Drop Move Duo Surface-mounted is a pendant lamp that consists of two height-adjustable lamps on a rectangular canopy. The cable length can be adjusted individually for each lamp from 50 cm to 200 cm. The light is focused by the lamps through frosted optical lenses and emitted homogeneously downwards. The two lamps are 60 cm apart from each other. The canopy is 80 cm long and rectangular. It is always supplied in the same finish as the lamps. On request, the pendant lamp is also available with a rounded canopy and with special lengths for the cables.

The Drop Move Duo Surface-mounted is offered in the surfaces polished aluminum, matt aluminum, bronze, white and matt black. All elements of the lamp are always in the same finish as the lamp itself. On request, lamps are also available in all finishes above with a topping in polished aluminum, matt aluminum, bronze, matt white and matt black.

The Drop Move Duo Surface-mounted is offered in three versions: dimmable on site with a trailing edge phase dimmer, DALI dimmable or with an integrated Casambi module. The DALI version requires a 5-core mains cable. With a Casambi module, the lamp can be operated via smartphone or tablet using the Casambi app via Bluetooth. Casambi technology also offers the option of switching and dimming several suitable lamps separately in groups.

When dimming the double pendant lamp, the light colour of the integrated LEDs changes to a warmer tone (from 3,000 Kelvin warm white to 1,800 Kelvin extra warm white) due to the used Dim-to-warm technology. LDM also offers a single, a triple or a quadruple lamp (on request) from the Drop series and the Drop with a shortenable, height-determinable cable.