

Byok

Piani Mono 165 Downlight




Oberfläche

- aluminium poli
- Matt aluminium
- noir mat

Leuchte

- réglable en hauteur
- réglable en hauteur

Technical details

Pays de fabrication	 Allemagne
Fabricant	Byok
Créateur	Kai Byok
Indice de protection / Indice IP	IP20
Contenu de la livraison	LED
aptitude de tension	230 - 240 Volt
matériel	aluminium
longueur de câble	300 cm
atténuation	dimmerable sur place avec commande gradateur de phase inverse
LED	y compris
Indice de rendu des couleurs	>90
La température de couleur en Kelvin	2.700 extra blanc chaud
remplacement des ampoules :	chez le fabricant / a l'usine
Les performances du système	10 x 3,6 Watt
Flux lumineux total en LM	3.060
Dimensions	H 1 cm B 5 cm L 165 cm

Description

The Byok Piani Mono 165 Downlight is a pendant lamp. The lamp body of the Piani Mono 165 Downlight is milled out of massive aluminum and polished or eloxated by hand afterwards. Ten LEDs are dazzle-free installed due to reflector technics and they may be exchanged singly.

Three surfaces are on offer: aluminum matt, aluminum polished or black matt. This pendant lamp is offered height-determinable (the cables can be set to the desired length during assembly) or height-adjustable (the total height can also be adjusted after assembly). The integrated LEDs can be **dimmed on site with a trailing edge phase dimmer**. On request, they are also available with gesture control and Dim2Warm technology. With gesture control, the light is dimmed by holding the hand flat under the lamp. With Dim2Warm technology, the light takes on a warmer colour when dimmed. When dimmed, the light colour of the LEDs changes from 2,700 Kelvin extra warm white to 2,100 Kelvin extra warm white. The dimming range is between 0 and 100 percent.