



Byok


Squadra Mono 200

Oberfläche

- aluminium poli
- Matt aluminium
- Aluminium noir
- satin poudre blanche enduite

Technical details

Pays de fabrication



Fabricant

Byok

Créateur

Kai Byok

Indice de protection / Indice IP

IP20

Contenu de la livraison

LED

aptitude de tension

230 - 240 Volt

matériel

aluminium

longueur de câble

250 cm

réglage de la hauteur

hauteur déterminée

atténuation

dimmerable sur place avec commande
gradateur de phase inverse

LED

y compris

Indice de rendu des couleurs

90

La température de couleur en Kelvin

2.700 extra blanc chaud

Les performances du système

12 x 3,6 Watt

Flux lumineux total en LM

3.670

répartition de la lumière

directement

Dimensions

H 4 cm | B 9 cm | L 200 cm

Description

The Byok Squadra Mono 200 is a pendant lamp with a clear and timeless design. The Squadra Mono consists of one element. Through this, the characteristic alignment is created. The hollow profile used, gets its effect through the mounting hooks installed to one side. The filigree steel ropes underline the purist optics.

The profile endings come with matt transparent and translucent end caps. That's why the Byok Squadra Mono 200 sets additional highlights when switched on. The integrated LEDs can be **dimmed on site with a trailing edge phase dimmer**. On request, they are also available with gesture control and Dim2Warm technology. With gesture control, the light is dimmed by holding the hand flat under the lamp. With Dim2Warm technology, the light takes on a warmer colour when dimmed. When dimmed, the light colour of the LEDs changes from 2,700 Kelvin extra warm white to 2,100 Kelvin extra warm white. The LEDs are placed in sockets enabling to singly exchange the bulbs.