




# Catellani & Smith

## Syphaduepassi Set 5

### Technical details

|  |  |
|--|--|
| <b>Pays de fabrication</b>                 |  Italie |
| <b>fabricant</b>                           | Catellani & Smith  |
| <b>concepteur</b>                          | Enzo Catellani   |
| <b>année</b>                               | 2018   |
| <b>protection</b>                          | IP44   |
| <b>Contenu de la livraison</b>             | LED  |
| <b>aptitude de tension</b>                 | 230 - 240 Volt   |
| <b>matériel</b>                            | laiton, verre  |
| <b>base/version</b>                        | G4   |
| <b>LED</b>                                 | y compris  |
| <b>Indice de rendu des couleurs</b>        | 80   |
| <b>La température de couleur en Kelvin</b> | 2.700 extra blanc chaud  |
| <b>remplacement des ampoules :</b>         | sur le site meme   |
| <b>Les performances du système</b>         | 5 x 1 Watt   |
| <b>Flux lumineux total en LM</b>           | 375  |
| <b>Dimensions</b>                          | H 2 x 45 + 3 x 75 cm   |

### Description

The Catellani & Smith Syphaduepassi Set 5 consists of five complete outdoor floor lamps, ready for connection, with all necessary accessories. With the Quick Connectors System from Catellani & Smith, the lamps can be easily connected together. Only a single power connection is required for installation. All necessary plug connections are included. The set contains:

- Two lamps with a height of 45 cm
- three lamps with a height of 75 cm
- an extension cable with a length of 500 cm
- a driver necessary for lamp operation

With their ground spike, the Syphaduepassi outdoor floor lamps can be fixed up to 25 cm into the ground. The heights of the lamps (45 cm and 75 cm) are indicated without ground spike. The glass lens of each lamp focuses the light and provides glare-free light. The brass lamp rod is bendable and can be realigned if necessary.

The Syphaduepassi lamps are protected to IP44 against water spray and solid foreign bodies with a diameter of 1 mm or more. The lamp rods are dust-tight with IP65 protection and protected against strong jets of water from any angle. Driver and extension cables are protected against temporary immersion with IP67 protection. The series also includes sets with one complete lamp or with two, three, four or nine complete lamps.