



Mawa

Seventies mounted spotlight Downlight LED dimmable

Oberfläche

- noir
- blanc

Farbtemperatur in Kelvin

- 2.700 extra blanc chaud
- 3.000 blanc chaud

Technical details

Pays de fabrication	 Allemagne
fabricant	Mawa
concepteur	Jan Blieske
concepteur 2	Jan Dinnebier
année	2020
protection	IP20
Contenu de la livraison	LED
aptitude de tension	230 - 240 Volt
Diamètre en cm	9
matériel	aluminium
angle du faisceau	30 degrees
atténuation	dimmerable sur place avec commande gradateur de phase inverse
Puissance en Watt	25 W
LED	y compris
Indice de rendu des couleurs	>90
Dimensions	H 18 cm Ø 9 cm

Description

The Mawa Seventies mounted spotlight Downlight LED emits its light directly and bundled downwards. The ceiling light has a height of 18.4 cm and a diameter of 9 cm. Thanks to its compact design, there are no visible screws. The lamp is offered in the powder-coated surfaces white or black matt. On request, it is also available in other RAL colours.

The Seventies mounted spotlight Downlight LED is offered with a colour temperature of 2,700 Kelvin extra warm white or 3,000 Kelvin warm white. On request, it is also available with 4,000 Kelvin white. This light can be dimmed on site with a trailing edge phase dimmer. A DALI dimmable version is also available on request. The lamp's colour rendering index is Ra >90, but it is also available with Ra >95 on request, which is closer to natural light (Ra 100).

The Seventies mounted spotlight Downlight LED has a beam angle of 30 degrees as standard. With a larger beam angle, the light is distributed over a larger area. Optionally, the cylindrical ceiling lamp can also be ordered with a beam angle of 16 or 22 degrees in the field Order Comment.