



# Mawa

## Mawa Wittenberg 4.0 ceiling lamp head-flush square LED US


### Oberfläche

- noir
- blanc

### Farbtemperatur in Kelvin

- 2.700 extra blanc chaud
- 3.000 blanc chaud
- 4.000 blanc

## Technical details

<b>Pays de fabrication</b>	 Allemagne
<b>Fabricant</b>	Mawa
<b>Créateur</b>	Jan Dinnebier
<b>année</b>	2021
<b>Indice de protection / Indice IP</b>	IP20
<b>Contenu de la livraison</b>	LED
<b>aptitude de tension</b>	110 - 125 Volt
<b>matériel</b>	aluminium
<b>angle du faisceau</b>	38 degrees
<b>atténuation</b>	1-10V dimmable
<b>LED</b>	y compris
<b>Indice de rendu des couleurs</b>	92
<b>tête de luminaire masse</b>	8 cm
<b>remplacement des ampoules :</b>	sur le site meme
<b>Les performances du système</b>	4 x 12,7 Watt
<b>Dimensions</b>	H 10 cm   B 22 cm   L 22 cm

## Description

The Mawa Wittenberg 4.0 ceiling lamp head-flush square LED has a square ceiling housing and four adjustable spotlight heads. The four lamp heads are integrated completely flush in the square ceiling housing, i.e. they disappear completely into the ceiling housing when folded in. The four lamp heads can be rotated separately by 365 degrees and swivelled by 90 degrees. The large light emission surface of the spotlight heads is well glare-reduced. The compact design of the lamp means that neither screws nor cables are visible. This ceiling lamp is available with a powder-coated matt white (RAL 9016) or matt black (RAL 9005) finish.

The integrated LEDs are offered with a colour temperature of 2,700 Kelvin extra warm white, 3,000 Kelvin warm white or 4,000 Kelvin white. On request, they are also available with dim-to-warm technology. With the dim-to-warm function, the light colour of the LEDs changes to a warmer tone when dimmed (from 3,100 Kelvin warm white to 1,850 Kelvin extra warm white). The Wittenberg 4.0 ceiling lamp head-flush square 4-lights LED can be 1-10V dimmed.

The spotlight has a beam angle of 38 degrees as standard. The beam angle determines the angle at which the light emerges from an LED spotlight. With a larger beam angle, the light is distributed over a larger area. Optionally, the lamp can also be ordered with a beam angle of 12 or 24 degrees in the Order comments field.