



Mawa

Wittenberg 4.0 ceiling lamp 2-lights LED

Oberfläche

- chroom
- zwart
- wit

Technical details

Land van fabricage	📕 Duitsland	The Mawa Witte
fabrikant	Mawa	heads, which ar
ontwerper	Jan Dinnebier	90 degrees and
ontwerper 2	mawa engineering	particularly larg
bescherming	IP20	design, neither s 2-lights LED is
Omvang van de levering	LED	chrome glossy s
voltage geschiktheid	230 - 240 Volt	The integrated
materiaal	aluminium, metaal	warm white and
stralingshoek	38 Graad	dimmer. On req
dimmen	dimbaar met fase- en fase-afsnijding en fase-regelingsdimmer	4,000 Kelvin wh Bluetooth or 1-1 lights LED is also
LED	inclusief	which is closer to
Kleurweergave-index	95	
Kleurtemperatuur in Kelvin	2.700 extra warm wit	The radiator has angle at which t angle, the light i
lampkop massa	8 cm	be ordered with
bulb vervangen:	ter plaatse zelf	
prestaties van het systeem	2 x 12,7 Watt	
Totale lichtstroom in lm	2.200	
lichtverdeling	direct	
Dimensions	H 9 cm B 8 cm L 18 cm	

Omschrijving

The Mawa Wittenberg 4.0 ceiling lamp 2-lights LED has two spotlight lamp heads, which are independently adjustable. Each lamp head can be swivelled 90 degrees and rotated 365 degrees. The light emission surface of this lamp is particularly large and well glare-free. With this compact, rectangular lamp design, neither screws nor cables are visible. The Wittenberg 4.0 ceiling lamp 2-lights LED is available in powder-coated white matt or black matt and chrome glossy surfaces. On request, the lamp is also offered with a black ceiling housing and lamp heads in chrome, brass or copper.

The integrated LEDs each have a colour temperature of 2,700 Kelvin extra warm white and can be dimmed on site with a leading or trailing edge phase dimmer. On request they are also available with 3,000 Kelvin warm white or 4,000 Kelvin white. In addition, the lamp is also on request on offer as DALI, Bluetooth or 1-10 volt dimmable versions. The Wittenberg 4.0 ceiling lamp 2-lights LED is also on request available with a colour rendering index of Ra 98, which is closer to natural light (Ra 100).

The radiator has a beam angle of 38 degrees. The beam angle determines the angle at which the light from an LED spotlight is emitted. With a larger beam angle, the light is distributed over a larger area. Optionally, the lamp can also be ordered with a beam angle of 12 or 24 degrees in the field Order Comment.

K-Meral GmbH & Co. KG | Sachsenweg 9 | Hambau / Öko-Zentrum NRW / Halle 4 | 59073 Hamm

Tel.: +49 (0) 2381 - 905 9350 | Fax: +49 (0) 2381 - 905 9310 | info@1001lights.com