



# Mawa

## Wittenberg 4.0 ceiling lamp semi-flush 3-lights LED

### Oberfläche

- zwart
- wit

### Technical details

|                            |   |
|----------------------------|---|
| Land van fabricage         |  Duitsland |
| fabrikant                  | Mawa  |
| ontwerper                  | Jan Dinnebier   |
| ontwerper 2                | mawa engineering  |
| bescherming                | IP20  |
| Omvang van de levering     | LED   |
| voltage geschiktheid       | 230 - 240 Volt  |
| materiaal                  | aluminium, metaal   |
| stralingshoek              | 38 Graad  |
| dimmen                     | dimbaar op locatie met faseafsnijding<br>dimmer   |
| LED                        | inclusief   |
| Kleurweergave-index        | 95  |
| Kleurtemperatuur in Kelvin | 2.700 extra warm wit  |
| lampkop massa              | 8 cm  |
| bulb vervangen:            | ter plaatse zelf  |
| prestaties van het systeem | 3 x 12,7 Watt   |
| Totale lichtstroom in lm   | 3.300   |
| Dimensions                 | H 10 cm   B 10 cm   L 30 cm   |

### Omschrijving

The Mawa Wittenberg 4.0 ceiling lamp semi-flush 3-lights LED has three spotlight lamp heads, which are individually adjustable. Each lamp head can be rotated 365 degrees and swivelled 90 degrees. The three lamp heads of this lamp are integrated half-flush into the ceiling housing. The light-emitting surface of the lamp heads is well glare-free and large. This lamp has a compact design in which neither screws nor cables are visible. The Wittenberg 4.0 ceiling lamp semi-flush 3-lights LED is available with powder-coated black matt and white matt surfaces. On request it is also offered with a black ceiling housing and lamp heads in chrome, brass or copper.

The integrated LEDs have a standard colour temperature of 2,700 Kelvin extra warm white, on request they are also available with 3,000 Kelvin warm white or 4,000 Kelvin white.

The radiator has a beam angle of 38 degrees. The beam angle determines the angle at which the light from an LED spotlight is emitted. With a larger beam angle, the light is distributed over a larger area. Optionally, the lamp can also be ordered with a beam angle of 12 or 24 degrees in the field Order Comment.