




# Knapstein

## ELSA-L

### Oberfläche

- messing
- nikkel

### Technical details

<b>Land van herkomst</b>	 Duitsland
<b>Fabrikant</b>	Knapstein
<b>Ontwerper</b>	Knapstein
<b>Beschermingsklasse / IP-bescherming</b>	IP20
<b>Leveringsomvang</b>	LED
<b>voltage geschiktheid</b>	230 - 240 Volt
<b>Projectie in cm</b>	57
<b>materiaal</b>	glas, messing
<b>dimmen</b>	Touch Dimmer op de lamphouder en touch dimmer op de lampkop
<b>LED</b>	inclusief
<b>Kleurweergave-index</b>	>90
<b>Kleurtemperatuur in Kelvin</b>	2.700 extra warm wit
<b>kandelaar Dimensions</b>	28 cm
<b>prestaties van het systeem</b>	1 x 28 Watt + 1 x 8,5 Watt
<b>Totale lichtstroom in lm</b>	5.215
<b>Dimensions</b>	H 185 cm

### Omschrijving

The Knapstein ELSA-L emits light upwards as a ceiling floodlight. The floor lamp also has a rotating and swivelling reading arm that can be realigned at any time. A further joint allows the lamp head on the reading arm to be swivelled independently of the arm. The uplight of the ceiling floodlight and the light of the lamp head can be switched separately and dimmed continuously via two push button dimmers. The push button dimmer for the uplight is integrated on the light rod. The push button dimmer for the light head is located on the head itself. The ELSA-L is available in the surfaces brass matt and nickel matt. The uplight has an opal, matt white glass. The floor lamp from Knapstein is also offered without reading arm.