

# Knapstein

## HELLI-2

#### Oberfläche

- nikkel
- zwart
- bronzen

#### Struktur#

- Nikkel
- zwart
- bronze

### **Technical details**

Land van fabricage

fabrikant

jaar

materiaal

hoogteverstelling

dimmen

Wattage

LED#

Kleurweergave-index

Lichtstroom in Im

Kleurtemperatuur in Kelvin

bescherming

Omvang van de levering

voltage geschiktheid

baldakijn

bulb vervangen: totale hoogte

Duitsland

Knapstein

2023

Acryl, Metall

hoogte verstelbaar

gebarencontrole

4x8 W

inclusief >90

4280

2.700 extra warm wit

IP20

LED

230 - 240 Volt

70x4,5 cm

bij de fabrikant / fabriek

70 - 170 cm

## **Omschrijving**

The Knapstein HELLI-2 LED pendant lamp has two cylindrical lamp bodies with freely combinable structures on the underside. The lenses of the lower diffusers are reversible, making it easy to choose between a lens for a focussed lighting effect and a disc for a diffuse lighting effect. To do this, unscrew the lower luminaire ring and replace the enclosed glass in the desired position (lens/disc). The aforementioned screw ring (structure) is available in 3 different colours. A swiping hand movement in the sensor area switches the corresponding light source on or off. To dim the light, the hand is held in front of the respective sensor until the desired light intensity is reached. Thanks to the integrated memory function, the last settings are saved and are immediately available again the next time the light is switched on. The uplight and downlight can be switched and dimmed separately using gesture control. Thanks to individual lift suspensions, the lamp bodies can be infinitely adjusted in height from approx. 70 cm - 170 cm at any time by simply pulling or lifting - even on sloping ceilings. The Knapstein HELLI-2 has a synchronisation function for adjusting the light intensity of all light sources on one side of the luminaire. The rectangular ceiling canopy of the Knapstein HELLI-2 LED pendant lamp has a magnetic holder, so no external screw connections are visible. This pendant lamp is available in several surfaces and freely combinable external structures on the underside.