

Byok

Piani Mono 165 Downlight




Oberfläche

- Aluminium polerowane
- Matt aluminium
- czarny matowy

Leuchte

- z regulacją wysokości
- z regulacją wysokości

Technical details

Kraj produkcji	 Niemcy
producent	Byok
projektant	Kai Byok
ochrona	IP20
zakres dostawy	LED
napięcie przydatność	230 - 240 Volt
tworzywo	aluminium
długość kabla	300 cm
ściemnianie	ściemniałna kontroli faz przyciemniania
LED	łącznie
Wskaźnik oddawania barw	>90
Temperatura barwowa w stopniach Kelvina	2.700 extra biała ciepła
wymiana żarówek:	u producenta / w fabryce
wydajność systemu	10 x 3,6 Watt
Całkowity strumień świetlny w lm	3.060
Dimensions	H 1 cm B 5 cm L 165 cm

Opis

The Byok Piani Mono 165 Downlight is a pendant lamp. The lamp body of the Piani Mono 165 Downlight is milled out of massive aluminum and polished or eloxated by hand afterwards. Ten LEDs are dazzle-free installed due to reflector technics and they may be exchanged singly.

Three surfaces are on offer: aluminum matt, aluminum polished or black matt. This pendant lamp is offered height-determinable (the cables can be set to the desired length during assembly) or height-adjustable (the total height can also be adjusted after assembly). The integrated LEDs can be **dimmed on site with a trailing edge phase dimmer**. On request, they are also available with gesture control and Dim2Warm technology. With gesture control, the light is dimmed by holding the hand flat under the lamp. With Dim2Warm technology, the light takes on a warmer colour when dimmed. When dimmed, the light colour of the LEDs changes from 2,700 Kelvin extra warm white to 2,100 Kelvin extra warm white. The dimming range is between 0 and 100 percent.