

Byok

Assiale L



Dimmbarkeit

- DALI ściemniania
- Czujnik zmierzchu i ruchu

Version

- obrotowe
- stałe

Technical details

Kraj produkcji	 Niemcy
Producent	Byok
Projektant	Kai Byok
Stopień ochrony / Stopień ochrony IP	IP20
Zawartość opakowania	LED
napięcie przydatność	230 - 240 Volt
tworzywo	aluminium
Moc (maks. W)	60 Watt
LED	łącznie
Wskaźnik oddawania barw	80
Temperatura barwowa w stopniach Kelvina	3.000 biała ciepła
Całkowity strumień świetlny w lm	4400 lm w dół, 4400 lm w górę
dystrybucja światła	bezpośrednio i pośrednio
Dimensions	H 48 cm B 7 cm L 180 cm

Opis

The Byok Assiale L is attached directly to the ceiling. It is available as fixed and rotatable. The joint of the rotating lamp is both flexible and robust. A spring-loaded mechanism protects the joint when the lamp is rotated.

The light is offered in anodized aluminum as well as on request powdered in RAL colours. The lamp is offered in three versions: on site DALI dimmable or controllable with light and motion sensors. It emits up- and downlight. In contrast to the Assiale T, this lamp has an L-shape.