


Luceplan

Counterbalance Floor



Technical details

Kraj produkcji	 Włochy
Producent	Luceplan
Projektant	Paolo Rizzatto
rok	2015
Stopień ochrony / Stopień ochrony IP	IP20
Zawartość opakowania	LED
napięcie przydatność	110 - 240 Volt
tworzywo	aluminium, cynk, stal
powierzchnia	czarny
ściemnianie	Przewód ściemniacza z suwakiem
skalowalność	na głowie oprawy
Moc w watach	16 W
LED	łącznie
Wskaźnik oddawania barw	90
Strumień świetlny w lm	598
Temperatura barwowa w stopniach Kelvina	2.700 extra biała ciepła
Średnica klosza	9 cm
świeczniku Wymiary	15 cm
Dimensions	H 170 cm

Opis

The Luceplan Counterbalance Floor has a rotating and traversable head. In addition, the lamp head can be adjusted at any time along the rod in its height. For this, neither screws nor other complicated handles have to be carried out. As a result, the light can also be used as a reading light. The lampshade, rod and base are all black. There is a dimmer included on the cable with which the light intensity can be dimmed. On the lamp head an on and off switch is placed. The light collection won the Compasso d'Oro ADI in the year 2014. Daniel Rybakken designed the collection for Luceplan.