

less'n'more

Zeus Wall / Ceiling Light Z-MDL1

Dimmbarkeit

- Dotknij Ściemniacz na baldachim
- ściemnialna kontroli faz przyciemniania

Oberfläche

- aluminium
- czarny
- biały

flexible_arm

- niebieski Tekstylia
- antracyt Tekstylia
- aluminium
- zielona Tekstylia
- czerwony Tekstylia
- brązowy Tekstylia
- białe Tekstylia
- noir Tekstylia

Technical details

Kraj produkcji

producent

projektant

ochrona

zakres dostawy

napięcie przydatność

tworzywo

kat nachylenia belki

Moc w watach

LED

Wskaźnik oddawania barw

Strumień świetlny w lm

Temperatura barwowa w stopniach

Kelvina

baldachim Wymiary

Głowica lampy Wymiary

wymiana żarówek:

Dimensions

Niemcy less'n'more less'n'more

IP43 LED

230 - 240 Volt aluminium, szkło

15 - 75 stopni

4,2 W

Łącznie

90

450

2.700 extra biała ciepła

10 cm

3 cm

na miejscu

L max. 23 cm

Opis

The Less'n'more Zeus Wall / Ceiling Light Z-MDL1 is built into the ceiling or wall. The recessed lamp has an aluminum mounting plate with a diameter of 10 cm as a canopy. It is mounted on a cavity wall box or flush mount box, **the external transformer is built into the ceiling or wall**.

The Zeus Wall / Ceiling Light Z-MDL1 has a flexible lamp arm that can be stretched and bent as required so that it can always be realigned. At maximum extension of the lamp arm, the lamp has a length of 23 cm. The flexible lamp arm is offered in these colours: aluminum, textile black, white, anthracite, blue, green, red and brown.

Lamp head and mounting plate are available in the surfaces aluminum and black. The beam angle of the light can be adjusted continuously between 15 and 75 degrees. To adjust the beam angle, the glass lens is turned out of or into the lamp head. The beam angle determines the angle at which the light emerges from an LED spotlight. The larger the beam angle, the larger the illuminated area, but it is also less bright because more area is illuminated.

An LED with a colour temperature of 2,700 Kelvin extra warm white is integrated in the lamp head. The Zeus wall and ceiling lamp is offered dimmable on site with a trailing edge phase dimmer or with a built-in push button dimmer on the mounting plate / canopy. The version with push button dimmer can be switched and dimmed via the push button. On request, the recessed lamp is also available with other colours for the lamp arm. In addition, a larger lamp of this series with a maximum length of 54 cm is also offered by Less'n'more.