

less'n'more

Zeus Wall / Ceiling Light Z-MDL1

Dimmbarkeit

- Dotknij Ściemniacz na baldachim
- ściemnialna kontroli faz przyciemniania

Oberfläche

- aluminium
- czarny
- biały

flexible_arm

- niebieski Tekstylija
- antracyt Tekstylija
- aluminium
- zielona Tekstylija
- czerwony Tekstylija
- brązowy Tekstylija
- białe Tekstylija
- noir Tekstylija

Opis

The Less'n'more Zeus Wall / Ceiling Light Z-MDL1 is built into the ceiling or wall. The recessed lamp has an aluminum mounting plate with a diameter of 10 cm as a canopy. It is mounted on a cavity wall box or flush mount box, **the external transformer is built into the ceiling or wall.**

The Zeus Wall / Ceiling Light Z-MDL1 has a flexible lamp arm that can be stretched and bent as required so that it can always be realigned. At maximum extension of the lamp arm, the lamp has a length of 23 cm. The flexible lamp arm is offered in these colours: aluminum, textile black, white, anthracite, blue, green, red and brown.

Lamp head and mounting plate are available in the surfaces aluminum and black. The beam angle of the light can be adjusted continuously between 15 and 75 degrees. To adjust the beam angle, the glass lens is turned out of or into the lamp head. The beam angle determines the angle at which the light emerges from an LED spotlight. The larger the beam angle, the larger the illuminated area, but it is also less bright because more area is illuminated.

An LED with a colour temperature of 2,700 Kelvin extra warm white is integrated in the lamp head. The Zeus wall and ceiling lamp is offered dimmable on site with a trailing edge phase dimmer or with a built-in push button dimmer on the mounting plate / canopy. The version with push button dimmer can be switched and dimmed via the push button. On request, the recessed lamp is also available with other colours for the lamp arm. In addition, a larger lamp of this series with a maximum length of 54 cm is also offered by Less'n'more.



Technical details

Kraj produkcji	 Niemcy
Producent	less'n'more
Projektant	less'n'more
Stopień ochrony / Stopień ochrony IP	IP43
Zawartość opakowania	LED
napięcie przydatność	230 - 240 Volt
tworzywo	aluminium, szkło
kąt nachylenia belki	15 - 75 stopni
Moc w watach	4,2 W
LED	łącznie
Wskaźnik oddawania barw	90
Strumień świetlny w lm	450
Temperatura barwowa w stopniach Kelvina	2.700 extra biała ciepła
baldachim Wymiary	10 cm
Głowica lampy Wymiary	3 cm
wymiana żarówek:	na miejscu
Dimensions	L max. 23 cm