

Lichtlauf

UpLight Down

Durchmesser in cm

- 40
- 50
- 30

Kabelfarbe

- czerwony
- biały
- szary



Technical details

Kraj produkcji	 Niemcy
Producent	Lichtlauf
Projektant	Christoph Matthias
rok	2012
Stopień ochrony / Stopień ochrony IP	IP20
Zawartość opakowania	Leuchtmittel/ Bulb
napięcie przydatność	110 - 240 Volt
tworzywo	polietylen, tekstylny
powierzchnia	biały
długość kabla	250 cm
ściemnianie	na miejscu z funkcją ściemniania
Cokół / Oprawka	E27
skalowalność	na smyczy
Moc (maks. W)	70 Watt
wymiana żarówek:	na miejscu

Opis

The UpLight Down light run is the floor version of the UpLight lamp. Supplemented with a stand ring and foot switch, this lamp illuminates low room zones with its mild light, creating a special and variable lighting mood. The white hollow sphere made of resistant and high-quality polyethylene is available in three different diameters, the textile cable in three different colours. The UpLight Down by Lichtlauf has an E27 ceramic socket and can be operated with conventional halogen bulbs as well as with LED retrofit bulbs. This portable lamp is available with a diameter of 30 cm, 40 cm or 50 cm. The textile 2.5 m cable is optionally available in white, red or grey. On request, the textile cable is also available in other colours and lengths.