

## Mawa

# Mawa Wittenberg 4.0 ceiling lamp head-flush square LED US

#### Oberfläche

- czarny
- biały

#### Farbtemperatur in Kelvin

- 2.700 extra biała ciepła
- 3.000 biała ciepła
- 4.000 biały

### **Technical details**

Kraj produkcji

producent

Mawa

projektant

Jan Dinnebier

rok

2021

ochrona IP20
zakres dostawy LED

napięcie przydatność 110 - 125 Volt tworzywo aluminium kąt nachylenia belki 38 stopni

**ściemnianie** 1-10V ściemniania

LEDŁącznieWskaźnik oddawania barw92Głowica lampy Wymiary8 cmwymiana żarówek:na miejscuwydajność systemu4 x 12,7 WattDimensionsH 10 cm | B 22 cm | L 22 cm

#### **Opis**

The Mawa Wittenberg 4.0 ceiling lamp head-flush square LED has a square ceiling housing and four adjustable spotlight heads. The four lamp heads are integrated completely flush in the square ceiling housing, i.e. they disappear completely into the ceiling housing when folded in. The four lamp heads can be rotated separately by 365 degrees and swivelled by 90 degrees. The large light emission surface of the spotlight heads is well glare-reduced. The compact design of the lamp means that neither screws nor cables are visible. This ceiling lamp is available with a powder-coated matt white (RAL 9016) or matt black (RAL 9005) finish.

The integrated LEDs are offered with a colour temperature of 2,700 Kelvin extra warm white, 3,000 Kelvin warm white or 4,000 Kelvin white. On request, they are also available with dim-to-warm technology. With the dim-to-warm function, the light colour of the LEDs changes to a warmer tone when dimmed (from 3,100 Kelvin warm white to 1,850 Kelvin extra warm white). The Wittenberg 4.0 ceiling lamp head-flush square 4-lights LED can be 1-10V dimmed.

The spotlight has a beam angle of 38 degrees as standard. The beam angle determines the angle at which the light emerges from an LED spotlight. With a larger beam angle, the light is distributed over a larger area. Optionally, the lamp can also be ordered with a beam angle of 12 or 24 degrees in the Order comments field.