



Mawa

Wittenberg 4.0 ceiling lamp head-flush 4-lights LED US

Oberfläche

- czarny
- biały

Farbtemperatur in Kelvin

- 2.700 extra biała ciepła
- 3.000 biała ciepła
- 4.000 biały

Technical details

Kraj produkcji	 Niemcy
Producent	Mawa
Projektant	Jan Dinnebier
rok	2021
Stopień ochrony / Stopień ochrony IP	IP20
Zawartość opakowania	LED
napięcie przydatność	110 - 125 Volt
tworzywo	aluminium
kąt nachylenia belki	38 stopni
ściemnianie	1-10V ściemniania
LED	łącznie
Wskaźnik oddawania barw	92
Głowica lampy Wymiary	8 cm
wymiana żarówek:	na miejscu
wydajność systemu	4 x 12,7 Watt
Dimensions	H 10 cm B 12 cm L 42 cm

Opis

The Mawa Wittenberg 4.0 ceiling lamp head-flush 4-lights LED has four individually adjustable spotlight heads. The lamp heads are integrated completely flush into the rectangular ceiling housing, i.e. they disappear completely into the ceiling housing when folded in. The four lamp heads can be rotated separately by 365 degrees and swivelled by 90 degrees. The large light emission surface of the spotlight heads is well glare-reduced. The compact design of the lamp means that neither screws nor cables are visible. This ceiling lamp is available with a powder-coated matt white (RAL 9016) or matt black (RAL 9005) surface finish.

The integrated LEDs are offered with a colour temperature of 2,700 Kelvin extra warm white, 3,000 Kelvin warm white or 4,000 Kelvin white. On request, they are also available with dim-to-warm technology. With the dim-to-warm function, the light colour of the LEDs changes to a warmer tone when dimmed (from 3,100 Kelvin warm white to 1,850 Kelvin extra warm white). The Wittenberg 4.0 ceiling lamp head-flush 4-lights LED can be 1-10 Volt dimmed by the customer. On request, it is also available as a DALI or by smartphone via Bluetooth dimmable version.

The spotlight has a beam angle of 38 degrees as standard. The beam angle determines the angle at which the light emerges from an LED spotlight. With a larger beam angle, the light is distributed over a larger area. Optionally, the lamp can also be ordered with a beam angle of 12 or 24 degrees in the Order comments field.